



## TROJAN TWIST / 352

Style	Hardtwist Cut Pile
Pile Content	100% Pure New Wool
Width	3.66m Broadloom
Pile Thickness	7.0 mm + - 10% AS/NZS 2111.1
Carpet Thickness	10.0 mm + - 10% AS/NZS 2111.1
Grading	Residential Extra Heavy Duty+Stairs 6 Stars – ACCS (92030) Contract Heavy Duty + Stairs 3 Stars – ACCS (92030)
Construction	Tufted
Environmental	ACCS ECS: Level 4
Insect Resistance	Treated With Insect Resist Agents
Primary Backing	Woven Polypropylene
Secondary Backing	Woven Jute
Pattern Repeat	Does not apply

**Installation:** It is recommended that this carpet be installed in accordance with Australian Standard AS 2455.1:2019 or New Zealand Standard NZS 2455.1:2007 unless otherwise specified. Cleaning and maintenance should be done in accordance with AS/NZS 3733:1995.

**Permanent Shading:** All cut pile carpets will in some circumstances exhibit the condition known as "Shading, Watermarking, or Pile Reversal". This condition is characterised by random light and dark patches appearing some weeks after installation, caused by the permanent reversal or bending of the carpet pile fibres with consequential different light effects. It cannot be predicted or prevented and appears to be related to the location of use rather than type of carpet construction or materials used. It does not affect the wear or durability of the carpet and since it is beyond the control of the manufacturer, it is not recognised as a manufacturing flaw or fault. You are urged to consider this characteristic before purchasing. Your Sales Executive can provide further information.

**Colour Variation:** Colour may vary from dye lot to dye lot.

**Material Variation:** Backing or other materials may change without notice depending on raw material availability.

**Custom Variation:** Custom weights and/or colours may be produced to meet individual requirements for larger projects. For further details contact your local Bremworth office.